

TECHNICAL SPECIFICATIONS

ACKCIO ANALOGUE NODES BEAM-AN-S1 & BEAM-AN-S4



MODELS

BEAM-AN-S1	Supports 1 sensor (2 analogue channels and 1 thermistor channel)
BEAM-AN-S4	Supports 4 sensors (8 analogue channels and 4 thermistor channels)

MECHANICAL

BEAM-AN-S1

BEAM-AN-S4

DIMENSION

100mm x 100mm x 80mm

220mm x 140mm x 80mm

WEIGHT

0.7kg

1.7kg

MATERIAL

Die-cast aluminium

Die-cast aluminium

ANALOGUE MEASUREMENTS

ADC

24-bit (22 true bit) low noise differential analogue-to-digital converters
Auto-calibration and auto-range
Sinc-3 filter for 50-60Hz supply rejection

MEASUREMENT RATE

50 SPS data acquisition with variable size moving average filter

MEASUREMENT DURATION

3.2 sec @ 50 samples per second with average filter size of 15

INSTRUMENT WARMUP

User-configurable
Min: 1s
Max: 2min

POWER SUPPLY OPTIONS FOR SENSORS

Configurable Output Power (PWR)
5V @ 100mA
12V @ 90mA
24V @ 40mA

Fixed Output Power
-12V @ -20mA (12VN)
5V @ 40mA (PBRG)

NOTE: All power modules are within $\pm 5\%$ tolerance

SPECIFICATIONS FOR VOLTAGE-OUTPUT SENSORS	Measurement Range: $\pm 10V$ Resolution: 0.0001V Accuracy: $\pm 0.05\%$ FS	
SPECIFICATIONS FOR CURRENT LOOP-OUTPUT SENSORS	Measurement Range: 0-20mA Resolution: 0.005mA Accuracy: $\pm 0.05\%$ FS	
SPECIFICATIONS FOR WHEATSTONE BRIDGE AND POTENTIOMETER SENSORS	Minimum Resistance: 150 Ohm Resolution: 0.1mV/V Accuracy: 0.25% FS	
SPECIFICATIONS FOR THERMISTOR	Measurement Range: $-20^{\circ}C$ to $+80^{\circ}C$ for 3K thermistor Resolution: $0.1^{\circ}C$ Accuracy: $\pm 0.2^{\circ}C$	
ABSOLUTE INPUT LIMITS	$\pm 12V$	
SUSTAINED INPUT VOLTAGE W/O DAMAGE	$\pm 10\%$ max (connector's input voltage from nominal value)	
INPUT	BEAM-AN-S1	BEAM-AN-S4
ANALOGUE DIFFERENTIAL INPUTS	2 differential inputs + 1 single-ended input (for thermistor)	8 differential inputs + 4 single-ended inputs (for thermistor)
WIRING	Push-in CAGE CLAMP (0.2 - 1.5 mm ² / 24 - 16 AWG)	
LOW-POWER MCU / PERIPHERALS		
MCU	Ultra-low power Arm [®] Cortex [®] -M3 48MHz 32-bit CPU	
MEMORY	128KB flash, 20KB ultra-low-leakage SRAM	
CLOCK	High-precision RTC self-compensated in temperature (10ppm from $-40^{\circ}C$ to $+80^{\circ}C$)	
ON-BOARD SENSORS	Temperature sensor (range: $-40^{\circ}C$ to $+80^{\circ}C$, resolution: $0.01^{\circ}C$, accuracy: $\pm 1.8^{\circ}C$) Barometer sensor (range: 300 to 1100hPa, resolution: 0.18Pa, accuracy: $\pm 1.7hPa$)	
EXTERNAL FLASH	8MB	
INTERFACES		
DISPLAY / KEYBOARD	LEDs	SYS - System status indication SENS - Sensing status indication
	Buttons	TEST - to test the Node RESET - to reset the Node FORMAT - to do a factory reset of the Node
USB DEVICE PORT	USB 2.0 full speed (Micro B connector) 5V, max 500 mA for mobile OTG	
IDC10 CONNECTOR	Only for firmware programming	

RF & MESH SPECIFICATIONS

RADIO BAND	ISM Band 863 - 870MHz, 902 - 928MHz	
TRANSMIT POWER	Up to 1 W (30 dBm)	
MODULATION	2-GFSK	
CERTIFICATIONS	BEAM-AN-S1 FCC: 2AT8M-AN-S1-V3X0 IC: 27349-ANS1V3X0 CE/RED Anatel (Brazil) MoC (Israel)	BEAM-AN-S4 FCC: 2AT8M-AN-S4-V3X0 IC: 27349-ANS4V3X0 CE/RED Anatel (Brazil)
ANTENNA	¼ λ stub antenna with SMA connector	
LINK DATA SPEED	50 kbps bitrate	
DATA SECURITY	AES128 encrypted end-to-end data	
HOPS	Up to 12	
NETWORK SIZE	Up to 50 Nodes	
RANGE*	Line-of-sight: Up to 5km Urban: Up to 1km Below ground: Up to 500m	

*Ranges are based on a transmission power of 30dbm. Actual transmission distances may vary depending on deployment conditions.

SOFTWARE & FIRMWARE

FIRMWARE	Ackcio Mesh: Ackcio's long-range low-power mesh networking firmware
SOFTWARE	Ackcio Nimbus: Android app for device setup, network monitoring, and troubleshooting

PROTECTION

CIRCUIT PROTECTION	Surge protection DC breakdown voltage 60V (± 20%@100V/μs) Impulse breakdown voltage 500V (@5kV/μs) typical Short circuit protection in power outputs Reverse supply protection
ESD	15kV

SYSTEM POWER REQUIREMENTS

SUPPLY VOLTAGE	2.7V to 4V	
INTERNAL NON-RECHARGEABLE BATTERIES	BEAM-AN-S1 1 x D-Cell Li-SOCl2 3.6V nominal voltage Recommended capacity 19Ah	BEAM-AN-S4 2 x D-Cell Li-SOCl2 3.6V nominal voltage Recommended capacity 19Ah
TYPICAL CURRENT DRAIN	<20μA in system idle <100mA in system RX mode <300mA in system TX mode (depends on output RF power setting)	

ENVIRONMENTAL CONDITIONS

OPERATING TEMPERATURE -40°C to +80°C

PROTECTION IP67

LIFETIME (MONTHS)

MODEL	SAMPLING FREQUENCY (MINS)						SENSOR	BATTERY
	5	10	15	30	60	360		
BEAM-AN-S1	12	15	16	17	18	18	Sensor 25mA @12V Excitation 1sec	1 x 19Ah D-Cell Li-SOCI2
BEAM-AN-S4	8	12	18	24	28	36	Sensor 25mA @12V Excitation 1sec	2 x 19Ah D-Cell Li-SOCI2

NOTE: Above table is for reference only. Estimation is done under typical Singapore weather conditions. The radio transmission power was set to 21dBm. Battery lifetimes might vary depending on deployment conditions and the formed wireless mesh topology.

MOUNTING BRACKETS / PLATES

BEAM-BK-SM

Small multi-purpose mounting bracket (vertical/horizontal/pole) with mounting screws

BEAM-BK-LG

Large multi-purpose mounting bracket (vertical/horizontal/pole) with mounting screws





Ackcio BEAM-AN-S1

with our **BEAM-BK-SM** small multi-purpose mounting bracket for vertical/horizontal or pole mounting



Ackcio BEAM-AN-S4

with our **BEAM-BK-LG** large multi-purpose mounting bracket for vertical/horizontal or pole mounting



Ackcio BEAM-AN-S1

Inner view



Ackcio BEAM-AN-S4

Inner view

DISCLAIMER: Specifications are subject to change without notice. In no event will Ackcio be liable for indirect, incidental or consequential damages arising from the use of this document.



+65 6802 7392
75 Ayer Rajah Crescent, #03-01/02,
Singapore 139953

linkedin.com/company/ackcio
sales@ackcio.com
www.ackcio.com



BEAM-TS-AN-2022-11